

**NEMA 4 CONNECTION HEAD WITH WELDED PROCESS CONNECTION**

**How to build a part number:**

To order an Applied Sensor Technologies temperature sensor, select the requirements for the categories listed below and fill in the corresponding boxes with your selection. Don't see exactly what you need? Give us a call!

SENSOR TYPE	ASSEMBLY STYLE	SHEATH DIAMETER	SHEATH MATERIAL	TEMPERATURE RANGE	SHEATH LENGTH	OPTIONS

**SENSOR TYPE** (See page 2-1b for optional elements)

**RTP1** – Platinum; DIN 0.00385; 100 ohm +/- 0.12% @ 0°C; 3-wire construction **(For dual element, add prefix "D", e.g., DRTP1)**

**ASSEMBLY STYLE**

**15 – Sheath with cast aluminum head and 1/2" NPT welded stainless steel process connection;** head conforms to NEMA 4 requirements; 3/4" NPT conduit connection; ceramic terminal block; gasketed screw cover with stainless steel chain

**SHEATH DIAMETER** (in inches) (see page 2-1b for restrictions)

- 4** – 1/8 (0.125)
- 6** – 3/16 (0.188)
- 7** – 1/4 (0.250)
- 9** – 3/8 (0.375)

**SHEATH MATERIAL**

**3** – 316 stainless steel


**TEMPERATURE RANGE** - Minimum and maximum operating temperatures

- 1** – -45 to 260°C (-50 to 500°F)
- 2** – -45 to 482°C (-50 to 900°F)
- 3** – -45 to 788°C (-50 to 1450°F)
- 4** – -200 to 260°C (-328 to 500°F)

**SHEATH LENGTH** (for lengths greater than L=36", consult AST)

**L#** – (e.g., L6 = 6 inch sheath)

**OPTIONS** – see page 2-1b



# STYLE 15

## AVAILABLE OPTIONS and MODIFICATIONS

ASSEMBLY OPTIONS		
Option Code	Description	
TAG1	Stainless steel tag and wire	
CAL1	NIST traceable calibration [specify point(s)]	
CRT1	Certificate of conformance	
WC20	Wiring cable gland for 0.187 - 0.312 diameter cables, for terminal heads with 1/2" NPT conduit connections	
WC21	Wiring cable gland for 0.125 - 0.187 diameter cables, for terminal heads with 1/2" NPT conduit connections	
TRANSMITTERS – For complete specs, see Transmitters section		
TR11	4-20 mA, 2-wire transmitter, single input, isolated output; specify range, units of measure (e.g., 0-200°C) and optional terminal head with *.	
TR12	4-20 mA, 2-wire transmitter, single input, non-isolated output; specify range and units of measure (e.g., 0-200°C) and terminal head with *.	
TR13	HART®/ 4-20 mA, 2-wire transmitter, single input, isolated output; specify range and units of measure (e.g., 0-200°C) and terminal head with *.	
OPTIONAL ELEMENTS		
RTDs are standardly platinum, 100-ohm, DIN-curve elements with a 0.00385 alpha.		
Option Code	Accuracy (at 0°C)	Construction
RTP1 (std.)	±0.12%	3-wire
RTP1A	<b>±0.06%</b>	3-wire
RTP1AA	<b>±0.01%</b>	3-wire
RTP6	±0.12%	<b>2-wire</b>
RTP7	±0.12%	<b>4-wire</b>
RTP7A	<b>±0.06%</b>	<b>4-wire</b>
RTP7AA	<b>±0.01%</b>	<b>4-wire</b>
Notes:		
1. For dual element, add prefix "D" (e.g., DRTP6)		
2. Additional materials, curves and resistance values are available - see Capabilities brochure.		

NEMA 4 OR 4X TERMINAL HEAD OPTIONS							
Head without ground screw	Head with internal ground screw	Process Connection	Conduit Connection				
Cast aluminum, screw cover with chain, NEMA 4							
HD10*	HD11*	1/2"	1/2"				
Std.*	HD13*	1/2"	3/4"				
Epoxy-coated aluminum, screw cover with chain, NEMA 4X							
HD50*	HD51*	1/2"	1/2"				
HD52*	HD53*	1/2"	3/4"				
Cast iron, screw cover with chain, NEMA 4							
HD20*	HD21*	1/2"	1/2"				
HD22*	HD23*	1/2"	3/4"				
316 stainless steel, screw cover with chain, NEMA 4X							
HD40*	HD41*	1/2"	3/4"				
White polypropylene, screw cover with chain, NEMA 4							
HD30	N/A	1/2"	3/4"				
Black polypropylene, screw cover with chain, NEMA 4							
HD31	N/A	1/2"	3/4"				
Nylon, screw cover							
HD32	N/A	1/2"	1/2"				
*can be used with transmitters							
Smallest Diameter Sheath Available By Sensor Type and Temperature Range							
SINGLE							
Temp Range	RTP 1	RTP 1A	RTP 1AA	RTP 6	RTP 7	RTP 7A	RTP 7AA
1	1/8	1/8	1/8	1/8	3/16	3/16	3/16
2	3/16	3/16	3/16	3/16	3/16	3/16	3/16
3	3/16			3/16	3/16		
4	1/8			1/8	3/16		
DUAL							
Temp Range	DRTP 1	DRTP 1A	DRTP 1AA	DRTP 6	DRTP 7	DRTP 7A	DRTP 7AA
1	3/16	3/16	3/16	3/16			
2	1/4	1/4	1/4	3/16			
3	1/4			1/4			
4	3/16			3/16			

### Notes:

1. See Accessories for additional information
2. For former Style 16, use option HD20
3. For former Style 29, use option HD32