

WASHER STYLE WITH LEADWIRE

How to build a part number:

To order an Applied Sensor Technologies temperature sensor, select the requirements for the categories listed below and fill in the corresponding boxes with your selection. Don't see exactly what you need? Give us a call!

SENSOR TYPE	ASSEMBLY STYLE	WASHER SIZE	WASHER MATERIAL	TEMPERATURE RANGE	SHEATH LENGTH	LEADWIRE LENGTH	OPTIONS

SENSOR TYPE (See page 2-16b for optional elements)

RTP1 – Platinum; DIN 0.00385; 100 ohm +/- 0.12% @ 0°C; 3-wire construction

(For dual element, add prefix "D"- e.g., DRTP1) (see page 2-16b for restrictions)

ASSEMBLY STYLE

32 – Washer with leadwire; Teflon® insulated conductors; armor cable; washer thickness 3/16" (0.188"); Sheath diameter 0.188" only

WASHER SIZE (in inches)

	Washer	
	ID	OD
6 – 3/16 (0.188)	0.193	0.375
7 – 1/4 (0.250)	0.255	0.500
9 – 3/8 (0.375)	0.380	0.750
10 – 1/2 (0.500)	0.510	1.000

WASHER MATERIAL

3 – stainless steel

TEMPERATURE RANGE - Minimum and maximum operating temperatures

1 – -45 to 260°C (-50 to 500°F)

2 – -45 to 482°C (-50 to 900°F)


SHEATH LENGTH (for lengths greater than L=36", consult AST)

L# – (e.g., L6 = 6 inch sheath)

LEADWIRE LENGTH

X# – (e.g., X6 = 6 inch length)

OPTIONS – see page 2-16b



Teflon® is a registered trademark of DuPont

STYLE 32

AVAILABLE OPTIONS and MODIFICATIONS

ASSEMBLY OPTIONS	
Option Code	Description
TAG1	Stainless steel tag and wire
CAL1	NIST traceable calibration [specify point(s)]
CRT1	Certificate of conformance
B45-	45° bend in sheath (specify length from tip in inches e.g., B45-6)
B90-	90° bend in sheath (specify length from tip in inches e.g., B90-6)
WIRING CONNECTION OPTIONS	
Option Code	Description
WC76	#6 spade terminals, plated copper
WC70	#10 spade terminals, plated copper
WC84	1/4" push-on insulated terminals, plated copper
WC90	#10 ring terminals
WC98	#8 ring terminals
PLUGS AND JACKS (Note: plug is designed to be attached to sensor assemblies. Jack options – for customer wiring – should only be specified if plug option is also included. Cable clamp is included for both plug and jack options.)	
PJ10	Standard plug, rated to 177°C (350°F)
PJ20	Standard jack, rated to 177°C (350°F)
BX CONNECTORS	
WC40	1/2"
WC50	3/4"

OPTIONAL ELEMENTS		
RTDs are standardly platinum, 100-ohm, DIN-curve elements with a 0.00385 alpha.		
Option Code	Accuracy (at 0°C)	Construction
RTP1 (std.)	±0.12%	3-wire
RTP1A	±0.06%	3-wire
RTP1AA	±0.01%	3-wire
RTP6	±0.12%	2-wire
RTP7	±0.12%	4-wire
RTP7A	±0.06%	4-wire
RTP7AA	±0.01%	4-wire
Notes:		
1. For dual element, add prefix "D" (e.g., DRTP6). Dual available on 2 and 3-wire constructions only.		
2. Additional materials, curves and resistance values are available - see Capabilities brochure.		