

DOUBLE-SIDED, SPRING-LOADED PROCESS MOUNTING WITH TERMINAL HEAD OPTIONS

How to build a part number:

To order an Applied Sensor Technologies temperature sensor, select the requirements for the categories listed below and fill in the corresponding boxes with your selection. Don't see exactly what you need? Give us a call!

SENSOR TYPE	ASSEMBLY STYLE	SHEATH DIAMETER	SHEATH MATERIAL	TEMPERATURE RANGE	SHEATH LENGTH	LEADWIRE LENGTH	OPTIONS

SENSOR TYPE (See page 2-6b for optional elements)

RTP1 – Platinum; DIN 0.00385; 100 ohm +/- 0.12% @ 0°C; 3-wire construction

(For dual element, add prefix "D"- e.g., DRTP1)

ASSEMBLY STYLE

75 – Sheath with double-sided, spring-loaded fitting; Teflon® insulated conductors; 1/2" NPT stainless steel connection. (Note: a variety of terminal heads may be added to this style – see page 2-6b)

SHEATH DIAMETER (in inches) (see page 2-6b for restrictions)

4 – 1/8 (0.125)

6 – 3/16 (0.188)

7 – 1/4 (0.250)

9 – 3/8 (0.375)

SHEATH MATERIAL

3 – 316 stainless steel

TEMPERATURE RANGE - Minimum and maximum operating temperatures

1 – -45 to 260°C (-50 to 500°F)

2 – -45 to 482°C (-50 to 900°F)

3 – -45 to 788°C (-50 to 1450°F)

4 – -200 to 260°C (-328 to 500°F)


SHEATH LENGTH (for lengths greater than L=36", consult AST)

L# – (e.g., L6 = 6 inch sheath)

LEADWIRE LENGTH

X# – (e.g., X3=3 inch length; X3 is standard if specifying a terminal head)

OPTIONS – see page 2-6b



STYLE 75

AVAILABLE OPTIONS and MODIFICATIONS

ASSEMBLY OPTIONS		
Option Code	Description	
TAG1	Stainless steel tag and wire	
CAL1	NIST traceable calibration [specify point(s)]	
CRT1	Certificate of conformance	
WC20	Wiring cable gland for 0.187 - 0.312 diameter cables, for terminal heads with 1/2" NPT conduit connections	
WC21	Wiring cable gland for 0.125 - 0.187 diameter cables, for terminal heads with 1/2" NPT conduit connections	
WIRING CONNECTION OPTIONS		
Option Code	Description	
WC76	#6 spade terminals, plated copper	
WC70	#10 spade terminals, plated copper	
WC84	1/4" push-on insulated terminals, plated copper	
WC90	#10 ring terminals	
WC98	#8 ring terminals	
TRANSMITTERS		
TR11	4-20 mA, 2-wire; single input; isolated output; specify range, units of measure (e.g., 0-200°C) and terminal head with *. See Accessories section for additional information.	
TR12	4-20 mA, 2-wire transmitter, single input, non-isolated output; specify range and units of measure (e.g., 0-200°C) and terminal head with *.	
TR13	HART®/ 4-20 mA, 2-wire transmitter, single input, isolated output; specify range and units of measure (e.g., 0-200°C) and terminal head with *.	
OPTIONAL ELEMENTS		
RTDs are standardly platinum, 100-ohm, DIN-curve elements with a 0.00385 alpha.		
Option Code	Accuracy (at 0°C)	Construction
RTP1 (std.)	±0.12%	3-wire
RTP1A	±0.06%	3-wire
RTP1AA	±0.01%	3-wire
RTP6	±0.12%	2-wire
RTP7	±0.12%	4-wire
RTP7A	±0.06%	4-wire
RTP7AA	±0.01%	4-wire
Notes: 1. For dual element, add prefix "D" (e.g., DRTP6) 2. Additional materials, curves and resistance values are available - see Capabilities brochure.		
EXPLOSION-PROOF TERMINAL HEAD OPTIONS		
Option Code	Process Connection	Conduit Connection
Cast aluminum, screw cover with chain; o-ring gasket rated to 100°C; ceramic terminal block; FM/CSA approved for Class I Div. 1, Groups B, C, D; Class II, Groups E, F, G; internal ground screw		
HD70*	1/2"	1/2"
HD71*	1/2"	3/4"
Epoxy-coated (same spec as HD70/HD71)		
HD80*	1/2"	1/2"
HD81*	1/2"	3/4"
Cast aluminum; ATEX approved for EEx d IIC; screw cover with chain; silicone rubber o-ring gasket; ceramic terminal block; rated for NEMA 4X, IP66 to IP68; internal and external ground screws		
HD72*	1/2"	1/2"
HD73*	1/2"	3/4"
Cast aluminum (formerly Style 60); screw cover; plastic terminal block; UL/CSA approved for Class I Div. 1, Groups C and D; Class II Groups E, F and G.		
HD60	1/2"	1/2"
HD61	1/2"	3/4"

NEMA 4 OR 4X TERMINAL HEAD OPTIONS							
Head without ground screw	Head with internal ground screw	Process Connection	Conduit Connection				
Cast aluminum, screw cover with chain, NEMA 4							
HD10*	HD11*	1/2"	1/2"				
HD12*	HD13*	1/2"	3/4"				
Epoxy-coated aluminum, screw cover with chain, NEMA 4X							
HD50*	HD51*	1/2"	1/2"				
HD52*	HD53*	1/2"	3/4"				
Cast iron, screw cover with chain, NEMA 4							
HD20*	HD21*	1/2"	1/2"				
HD22*	HD23*	1/2"	3/4"				
316 stainless steel, screw cover with chain, NEMA 4X							
HD40*	HD41*	1/2"	3/4"				
White polypropylene, screw cover with chain, NEMA 4							
HD30	N/A	1/2"	3/4"				
Black polypropylene, screw cover with chain, NEMA 4							
HD31	N/A	1/2"	3/4"				
Nylon, screw cover							
HD32	N/A	1/2"	1/2"				
*can be used with transmitterS							
Smallest Diameter Sheath Available By Sensor Type and Temperature Range							
SINGLE							
Temp Range	RTP 1	RTP 1A	RTP 1AA	RTP 6	RTP 7	RTP 7A	RTP 7AA
1	1/8	1/8	1/8	1/8	3/16	3/16	3/16
2	3/16	3/16	3/16	3/16	3/16	3/16	3/16
3	3/16			3/16	3/16		
4	1/8			1/8	3/16		
DUAL							
Temp Range	DRTP 1	DRTP 1A	DRTP 1AA	DRTP 6	DRTP 7	DRTP 7A	DRTP 7AA
1	3/16	3/16	3/16	3/16			
2	1/4	1/4	1/4	3/16			
3	1/4			1/4			
4	3/16			3/16			

THERMOWELLS & PROTECTION TUBES

For a complete offering of metal, ceramic and composite material thermowells and protection tubes, please see the Thermowell and Protection Tube sections.

Note: Many non-standard options, including additional sheath diameters and materials, may also be available – consult AST for specific requirements. HART® is a registered trademark of the HART Communication Foundation.

