

Company Name: \_\_\_\_\_  
Ship To: \_\_\_\_\_

City/ST/Zip: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Phone: \_\_\_\_\_

P.O.#: \_\_\_\_\_

Qty	RTD Sensor Pods (100-ohm, Class B, 0.00385 alpha with 48" leads)	
	Part Number	Description
<i>Pods for 0.250" O.D. Housings</i>		
	RT1254	3-wire, fiberglass insulation (std)
	RT1260	3-wire, Teflon insulation (std)
	RT1257	4-wire, Teflon insulation
	RT1276	4-wire, fiberglass insulation
<i>Pods for 0.188" O.D. Housings</i>		
	RT1184	3-wire, fiberglass insulation
	RT1256	3-wire, Teflon insulation
Thermocouple Sensor Pods* (standard limits of error with 48" leads)		
<i>Pods for 0.250" O.D. Housings</i>		
	MI1113__	Fiberglass insulation (specify J, K, E or T calibration and grounded or ungrounded junction [G or U]; e.g., MI1113KU)
	MI1113TF__	Teflon insulation (specify J, K, E or T calibration and grounded or ungrounded junction [G or U]; e.g., MI1113TFJU)
<i>Pods for 0.188" O.D. Housings</i>		
	MI1115__	Fiberglass insulation (specify J, K, E or T calibration grounded or ungrounded junction [G or U]; e.g., MI1115KU)
	MI1115TF__	Teflon insulation (specify J, K, E or T calibration grounded or ungrounded junction [G or U]; e.g., MI1115TFJU)
*For dual element, specify as JJ, KK, EE or TT		
Housings (stainless steel, one closed end)		
	HS2512	0.250" O.D. x 12" long
	HS2524	0.250" O.D. x 24" long (std. with kit)
	HS2536	0.250" O.D. x 36" long
	HS2548	0.250" O.D. x 48" long
	HS1812	0.188" O.D. x 12" long
	HS1824	0.188" O.D. x 24" long
	HS1836	0.188" O.D. x 36" long
	HS1848	0.188" O.D. x 48" long
Compression Fittings		
<i>For 0.250" housings</i>		
	PF65	1/4" NPT, 316 stainless steel body and ferrule
	PF66	1/4" NPT, 316 stainless steel body; Teflon ferrule
	PF73	1/2" NPT, 316 stainless steel body and ferrule
	PF74	1/2" NPT, 316 stainless steel body; Teflon ferrule
<i>For 0.188" housings</i>		
	PF55	1/4" NPT, 316 stainless steel body and ferrule
	PF56	1/4" NPT, 316 stainless steel body; Teflon ferrule
	PF59	1/2" NPT, 316 stainless steel body and ferrule
	PF60	1/2" NPT, 316 stainless steel body; Teflon ferrule
Unions (1/2" NPT)		
	UC1011	Carbon steel, ordinary location
	US1011	Stainless steel, ordinary location



## REPLACEMENT PARTS RE-ORDER FORM

Qty	Terminal Heads with 4-Post Terminal Block Included (1/2" NPT process conn.)	
	Part Number	Description
	PH01	1/2" Aluminum, ordinary locations
	PH02	3/4" Aluminum, ordinary locations (Std. with kit)
	PH04	1/2" Cast iron, ordinary locations
	PH05	3/4" Cast iron, ordinary locations
	PH23	3/4" Black polypropylene, ordinary locations
	PH24	3/4" White polypropylene, ordinary locations
	PH47	3/4" 316 stainless steel, ordinary locations
	PH50	1/2" Aluminum, explosion-proof, 3-post block
	PH51	3/4" Aluminum, explosion-proof, 3-post block
Terminal Blocks		
	Part Number	Description
	PH44	4-post, ceramic
	PH48	3-post, ceramic, for PH50 and PH51 heads
Carbon Steel Nipples (1/2" NPT)		
	NC1001	1" long
	NC1002	2" long
	NC1003	3" long
	NC1004	4" long
	NC1006	6" long
Stainless Steel Nipples (1/2" NPT)		
	NS1001	1" long
	NS1002	2" long
	NS1003	3" long
	NS1004	4" long
	NS1006	6" long
Spring-Loaded Kits		
	AC1088	For 0.188" housings
	AC1087	For 0.250" housings
Spring-Loaded Hex Fittings		
	PF14	Stainless steel, for 0.250" housings
	PF13	Stainless steel, for 0.188" housings
Plugs and Jacks		
	PT05-	Thermocouple plug (specify J, K, E or T); e.g., PT05-J
	PT05-3	3-pin RTD plug
	PT06-	Thermocouple jack (specify J, K, E or T); e.g., PT06-K
	PT06-3	3-pin RTD jack
	PT10	Wire clamp
	B1250	Brass crimp insert, for 0.250" housings
	B1188	Brass crimp insert, for 0.188" housings
Strain Reliefs (Bag of 10)		
	TS1092	Nylon grommet for 0.250" housings
	TS1094	Teflon strain relief for 0.188" housings
Armor Cable Kit		
	TS1093	3' stainless armor and adaptor for 0.250" housings